

TRX S26

The TRX S26 is a rail certified, 26-port managed switch based on Cisco IOS technology.

It provides Enterprise switching for maximum performance in high-throughput applications such as Passenger Wi-Fi and infotainment.



26-port Cisco switch for rail

Key Features

- Enterprise grade Cisco IOS Layer 2/3 switch
- Supports Gigabit Copper/Fiber train backbone
- Fail-to-wire on Gigabit ports to maintain service to downstream cars during outage
- Extensive security features including 802.1x authentication, Port Security, ACLs
- PoE compatible with IP cameras and Wi-Fi access points
- Extensive Quality of Service features for video streaming



Trains



Autonomous



Fleet

EMEA:
Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
DO8 ET1W.
Tel: +353 1 6624270

US
Klas Government,
1101 30th Street NW,
Suite 500, Washington,
DC 20007.
Tel: +1 202-625-8315



www.klasgroup.com

KLAS

TRX S26

Specifications

 Cisco Technology



Physical Specifications

- 9.8"W x 7.7"L x 3"H (250 mm x 195 mm x 77 mm)
- 7.6 lb / 3.45 kg

Ports

- 2 Gigabit Ethernet ports available as X-code M12 Copper or QODC fiber. Fail-to-wire enabled
- 8 Fast Ethernet ports available as X-code M12 Copper on front panel. All ports are PoE+ enabled and powered from 24-110V supply
- Additional 16 Fast Ethernet ports available as X-Code M12 Copper on rear panel. Ports are PoE+ enabled when external 48V DC is supplied
- RJ-45 console port behind cover plate
- Extruded aluminium enclosure

Standards Compliance

- 2011/65/EC (RoHS 2)

- REACH (EC 1907/2006)
- EN50155:2017 Railway Applications - Electronic equipment used on rolling stock; EN50155: Heat, Cold, Insulation, Vibration and Shock; EN60068-2-1, EN60068-2-2, EN60068-2-30
- EN61373:2017 Railway Applications - Rolling stock equipment - Shock and Vibration Tests
- EN50121-3-2:2017 Railway Applications - Electromagnetic Compatibility - Part 3-2 Rolling Stock - Apparatus
- EN45545-2:2015 Railway Applications - Fire Protection on Railway Vehicles - Part 2
- EN60529 - Degrees of protection provided by enclosures (IP Code)
- IP66 Compliant
- 130 W when front panel PoE ports are in use
- 330 W when front and rear panel PoE ports are in use
- 48 VDC Input to power additional 16 PoE ports

- EN61373:2017 Railway Applications - Rolling stock equipment - Shock and Vibration Tests
- EN50121-3-2:2017 Railway Applications - Electromagnetic Compatibility - Part 3-2 Rolling Stock - Apparatus
- EN45545-2:2015 Railway Applications - Fire Protection on Railway Vehicles - Part 2
- EN60529 - Degrees of protection provided by enclosures (IP Code)
- IP66 Compliant

Electrical Specifications

- 24 - 110 VDC
- Power consumption
 - 14 W without PoE

Cisco IOS Features

- Port security
- 802.1x authentication
- 802.1q VLANs
- Multicast support with IGMP snooping
- IPv4 and IPv6
- DHCP server
- Spanning Tree Protocol (STP) 802.1x authentication
- 802.1q VLANs
- Multicast support with IGMP snooping
- IPv4 and IPv6
- DHCP server
- Spanning Tree Protocol (STP)



TRX® S26 Front



TRX® S26 Rear

KEELOS | **BLACKROCK**

Optimised Management & Virtualization

EMEA:
Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
DO8 ET1W.
Tel: +353 1 6624270

US
Klas Government,
1101 30th Street NW,
Suite 500, Washington,
DC 20007.
Tel: +1 202-625-8315



www.klasgroup.com

KLAS